

**OPTIONS****Flow Rate**

- 0.35 gpm (1.3 Lpm) (0.35GPM)
- 1.0 gpm (3.8 Lpm) (1.0GPM)
- 1.5 gpm (5.7 Lpm) (1.5GPM)
- 2.2 gpm (8.3 Lpm) (2.2GPM)
- 0.5 gpm (1.9 Lpm) (0.5GPM)

**Spray Type**

- Laminar (LAM)
- Multi-Laminar (MLM)

**Mixer**

- Back-Check Tee (TEE)
- Below Deck Manual Mixing Valve (BDM)

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.



Image for a standard SF-2250 shown

**DESCRIPTION**

Sloan® Battery-Powered Deck-Mounted Gooseneck Body Faucet

**FEATURES**




Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Gooseneck Hand Washing Faucet with the following features:

- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

**DOWNLOADS**

- [SF Series Installation Instructions](#)
- [SF Series \(FR\) Installation Instructions](#)
- [SF Series \(SP\) Installation Instructions](#)
- [SFP 35-A Installation Instructions](#)
- [Trim Plate Guide](#)
- [SF-2100/2150 and SF-2200/SF-2250 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

**VIDEOS**

-  [SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Parts Breakdown](#)
-  [SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Module Replacement](#)
-  [SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Battery Replacement- Sensor Range Adjustment](#)