

**CODE NUMBER**

34000006

**DESCRIPTION**

6/3 Lpf, Filtered, Yellow Brass Finish, Fixture Connection Rear Spud, Dual Flush, TruFlush Concealed Manual Water Closet Flushometer.

**DETAILS**

- Flush Volume: 6/3 Lpf (1.6/0.8 gpf)
- Finish: Yellow Brass
- Bypass: Filtered
- Fixture Type: Water Closet
- Fixture Connection: Rear Spud

**FEATURES**

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Vandal-resistant wall plate with easy-to-push button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate

**RECOMMENDED SPECIFICATION**

Valve shall be concealed with front access wall plate smaller than 7" x 7" and shall have integrated control stop.

**VALVE OPERATING PRESSURE (FLOWING)**

20-80 PSI (138-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

**DOWNLOADS**

- [TRF-1036-N, 1024-N Manual Dual Flush India Installation Instructions - India](#)
- [TRF-1000 Manual Dual Flush Wall Plate Installation Instructions - India](#)
- [TRF-1036-N, 1024-N Manual Dual Flush Valve Repair and Maintenance Guide - India](#)

**NOTES**

All information contained within this document subject to change without notice.

Looking for other variations of the TRF-1036-N product? [View the general spec sheet with all options.](#)